



## **HIGH SPEED DOORS**

## CARRINGTON DOORS

HORTON STREET, HIGHER HILLGATE, STOCKPORT, SK1 3LR

TEL: 0161 477 3391 - FAX: 0161 477 3392

Email: sales@carringtondoors.co.uk - Web: www.carringtondoors.co.uk



Horton Street Higher Hillgate Stockport SK1 3LR

Tel: 0161 477 3391 - Fax: 0161 477 3392

Email: sales@carringtondoors.co.uk
Web: www.carringtondoors.co.uk

## **HIGH SPEED DOORS**

These superior high-speed doors are used both inside and as exterior doors to optimise the flow of traffic, improve room conditions and save energy.

Thanks to standard equipment with an FU frequency converter control and safety light grille, all our high speed doors are exceptionally long lasting and easy to service.

Manufactured and certified in line with stringent European standards.



Spring steel endlock



Soft edge bottom profile with integrated radio crash spring switch.

EXTERNAL DOOR			
Size Range	Max. width (LDB) - 5000 mm	Max. height (LDH) - 6000 mm	
Speed	With std FU control BK 150FUE H	Max Opening speed - 2.0 m/sec.	Max closing speed - 0.8 m/sec
	Optional control AS 500 FU E	Max Opening speed - 3.0 m/sec.	Max closing speed - 0.8 m/sec
Operation	Push Button Control Panel	Induction Loops, Radio Control, Radar – POA	
Emergency opening	Crank handle		
Curtain	Spring steel windlock with lateral twin rollers and tensioning system	Fabric thickness – 1.5 mm	Vision panel thickness – 2.0 mm
Resistance to wind load (EN 12424)	Class 2 – 100 km/h		
Curtain colours	RAL 1018 Zinc Yellow	RAL 2004 Pure Orange	RAL 3002 Carmine Red
	RAL 5010 Gentian Blue	RAL 7038 Agate Grey	
Safety Light Grille	Included as standard		

Our policy is one of continuous product development and we therefore reserve the right to vary the product specification in this sales brochure.